



Fine Ribbed Rubber Matting to ASTM D178 Type 1 Class4

SKU: SM555

SM555 Fine Ribbed Rubber Matting to ASTM D178 Type 1 Class4, is a high quality electrical safety matting fully tested to 30,000 volts with the regulation standard, stamped on the reverse of the roll at 1000mm intervals.

Dielectric test voltage: 50,000 volts,

Surface proof tested: 40,000v

maximum safety working voltage of 36,000v.

It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.

- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance
- THIS GRADE DOES NOT CONTAIN RECYCLED RUBBER

Cut lengths available to order. SM555 can also be supplied to order in colours and flame retardant, low smoke emission grades

TECHNICAL DATA

STOCK ROLL SIZES [M X M X MM]	WEIGHT [KG/M2]
10m x 0.91m x 12.7mm	16.51

SPECIFICATIONS COMPOUND

SPECIFICATIONS COMPOUND	VALUES [TYPICAL]
Colour	Black
Compound:	NR
Hardness Shore 'A' (± 5)	70
Density (S.G.)	1.5
Tensile Strength (Kg/cm ²)	40
Elongation at break (%)	200
Abrasion Resistance [mm ³]	180 mm ³
Minimum Temperature	-20°C
Maximum Temperature	+70°C
Test Voltage (See Data)	50kv
Standard	ASTM

Metroseal Datasheet Disclaimer: All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.